

## OVERVIEW

**Terralite Granite is a granite effect exterior coating based on pure acrylic polymers and mineral aggregate. It is applied by spray to achieve a hammer finish granite effect which is extremely authentic. It is available in a range of 10 granite finishes.**

## PROPERTIES

Terralite Granite is based on decorative aggregate mica, coloured stone, acrylic polymers and additives with the following properties:

- Highly water and weather resistant
- Washable
- Abrasion resistant
- Algae and fungi resistant
- UV stable coating
- Highly decorative finish

## AREAS OF USE

Exterior and interior facades of concrete, cement rendering and wood, on commercial and industrial complexes, housing complexes and is particularly effective in areas of severe climatic exposure. Ideal as an EIFS finish,

## PREPARATION OF SURFACE

**New surfaces:** Ensure that all dust, dirt and foreign matter are brushed and scraped away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with a Handycoat Exterior.

**Old surfaces:** Before applying Terralite to old surfaces, ensure the substrate is firm. First wash down the surface with a soda/water solution, rinse and allow to dry before repairing or applying the first coat.

Prime surfaces with a coat of Penetrating Primer prior to application of finish.

## APPLICATION & CLEANING OF TOOLS

Terralite Granite undercoat is applied to unify the substrate colour at a rate of 300gm/m<sup>2</sup> by roller. Allow to dry for 4 hours before applying Terralite Granite.

Terralite Granite is applied by hopper gun to create a hammer finish granite effect at a rate of 2.0-3.0kg/m<sup>2</sup> and allowed to dry for 24 hours.

Apply a topcoat of Terracoat Topcoat to seal surface.

Clean tools and equipment with water after use.

## HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

## PACKAGING & STORAGE

Terralite Granite is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

**TECHNICAL DATA**

<b>Product</b>	Granite effect exterior coating.
<b>Binder</b>	Pure acrylic.
<b>Filler Material</b>	Coloured stone, flake, mica.
<b>Additives</b>	Chemical resistant and adhesion promoting agents.
<b>Coating Thickness</b>	1.5-2.0mm
<b>Consumption</b>	2-3Kg/m <sup>2</sup>
<b>Specific Gravity</b>	1.70
<b>Colour</b>	10 granite finishes.
<b>Packaging</b>	25kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

**CHINA:**

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**

Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**EGYPT:**
**Terraco Egypt Chemical Industries S.A.E.**

Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

**JORDAN:**
**Jordan Swedish Polymers Industrial Corp.**

Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

**IRELAND:**
**Terraco Technical Centre, Ireland**

Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

**PAKISTAN:**

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

**ROMANIA:**

**Terraco Romania SRL**  
 Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

**RUSSIA:**

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terrakovostok.ru  
 Web: www.terraco.com

**SOUTH KOREA:**

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

**THAILAND:**

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

**TURKEY:**

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

**UAE:**

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

**UK:**

**ADDAGRIP**  
 Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

**VIETNAM:**

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com